

AMENDMENTS TO THE CLAIMS

1. (Currently amended) A method of controlling usage of network resources on a communications network based on the identity of an authenticated user, the method comprising acts of:

~~(a)~~ creating one or more packet rules for analyzing packets received at one or more network devices of the communications network, each rule including a condition and action to be taken as part of providing a service of the communications network if a packet received at a device satisfies the condition, wherein the one or more packet rules are defined to examine any portion of a packet;

~~(b)~~ storing the one or more packet rules;

~~(c)~~ ~~in response to a user,~~ creating one or more service abstractions, each service abstraction representing a communications network service to be provided to users of the communications network, each service abstraction including a named set of one or more of the packet rules that, in combination, provide the represented communications network service;

~~(d)~~ storing the one or more service abstractions;

associating the one or more service abstractions with the identity of the authenticated user of the communications network; and

~~(e)~~ ~~associating one or more of the service abstractions with an authenticated user of the communications network to control usage of network resources on the communications network by the authenticated user~~ in response to receipt of a packet at any of the network devices from the authenticated user, using the one or more service abstractions associated with the identity of the authenticated user to control usage of network resources on the communications network, the using including applying the packet rules in the one or more service abstractions to the packet.

2. (Currently amended) The method of claim 1, further comprising an act of:

~~(f)~~ configuring a network device of the communications network with one or more packet rules according to at least one of the service abstractions.

3. (Currently amended) The method of claim 2, wherein ~~the act (f) configuring the network device~~ comprises: configuring a port module of a switching device of the communications network with one or more packet rules according to at least one of the service abstractions.

4. (Cancelled)

5. (Currently amended) The method of claim 1, further comprising an act of:

~~(f)~~ distributing the one or more service abstractions to one or more network devices residing on the communications network.

6. (Cancelled)

7. (Currently amended) The method of claim 1, further comprising an act of:

~~(f)~~ creating one or more role abstractions ~~associated with an authenticated user~~, each role abstraction representing a role of ~~the authenticated users~~ with respect to the communications network, and each role abstraction including a set of one or more service abstractions representing communications network services to be provided to users associated with the represented role,

and wherein the act of associating one or more service abstractions with the identity of the authenticated user includes associating the identity of the authenticated user with one or more of the role abstractions.

8. (Currently amended) The method of claim 7, further comprising an act of:

~~(g)~~ configuring a network device of the communications network with one or more packet rules according to one of the role abstractions.

9. (Currently amended) The method of claim 8, wherein ~~act (g)~~ configuring the network device with one or more packet rules according to one of the role abstractions comprises: configuring a port module of a switching device of the communications network with one or more packet rules according to one of the role abstractions.

10. (Cancelled)

11. (Currently amended) The method of claim 7, further comprising an act of:

(g) distributing the one or more role abstractions to one or more network devices residing on the communications network.

12. (Cancelled)

13. (Currently amended) A system for enabling a network manager to controlling usage of network resources on a communications network based on the ~~identify~~ identity of an authenticated user, the system comprising:

a rule editing module enabling the network manager to create ~~edit~~ one or more packet rules for analyzing packets received at one or more devices of the communications network, each rule including a condition and action to be taken if a packet received at a device satisfies the condition, ~~wherein the one or more packet rules are defined to examine any portion of a packet;~~

a service editing module enabling the network manager to create, ~~in response to a user,~~ edit one or more service abstractions ~~associated with an authenticated user of the communications network for controlling usage of network resources on the communications network by the authenticated user,~~ each service abstraction representing a communications network service to be provided to users of the communications network, each service abstraction including a named set of one or more of the packet rules that, in combination, provide the represented communications network service;

a user management module enabling the network manager to associate users of the communications network with one or more of the service abstractions;

and

storage means for storing one or more ~~created~~ of the service abstractions ~~or,~~ one or more ~~created~~ of the packet rules or one or more of the associations between users of the communications network and one or more of the service abstractions.

14. (Original) The system of claim 13, further comprising: logic to configure a network device with one or more packet rules according to at least one of the service abstractions.

15. (Original) The system of claim 14, wherein the logic comprises: port configuration logic to configure a port module of a switching device with one or more packet rules according to at least

one of the service abstractions.

16. (Cancelled)

17. (Original) The system of claim 13, further comprising: a distribution module to distribute the one or more service abstractions to one or more network devices residing on the communications network.

18. (Cancelled)

19. (Currently amended) The system of claim 13, further comprising:

a role editing module enabling the network manager to ~~create~~ edit one or more role abstractions ~~associated with an authenticated user~~, each role abstraction representing a role of ~~an authenticated~~ users with respect to the communications network, and each role abstraction including a set of one or more service abstractions representing communications network services to be provided to users associated with the represented role,

and wherein the user management module further enables the network manager to associate users of the communications network with one or more of the role abstractions.

20. (Original) The system of claim 19, further comprising: logic to configure a network device with one or more packet rules according to one of the role abstractions.

21. (Original) The system of claim 20, wherein the logic comprises: port configuration logic to configure a port module of a switching device with one or more packet rules according to one of the role abstractions.

22. (Cancelled)

23. (Original) The system of claim 19, further comprising: a distribution module to distribute the one or more role abstractions to one or more network devices residing on the communications network.

24. (Cancelled)

25. (Cancelled)

26. (Currently amended) A computer program product, comprising: a computer readable medium; and computer readable signals stored on the computer readable medium that define instructions that, as a result of being executed by a computer, instruct the computer to perform a process of controlling usage of network resources on a communications network based on the identity of an authenticated user, the process comprising acts of:

~~-(a) creating one or more packet rules for analyzing packets received at one or more devices of the communication network, each rule including a condition and action to be taken as part of providing a service of the communications network if a packet received at a device satisfies the condition, wherein the one or more packet rules are defined to examine any portion of a packet;~~

~~-(b) storing the one or more packet rules;~~

~~-(c) in response to a user, creating one or more service abstractions associated with an authenticated user of the communications network for controlling usage of network resources on the communications network by the authenticated user, each service abstraction representing a communications network service to be provided to users of the communications network, each service abstraction including a named set of one or more of the packet rules that, in combination, provide the represented communications network service; and~~

~~-(d) storing the one or more service abstractions.~~

27. (Currently amended) A method of controlling usage of network resources on a communications network based on the identity of an authenticated user, the method comprising acts of:

(a) defining one or more packet rules for analyzing packets received at one or more devices of the communications network, each rule including a condition and action to be taken if a packet received at a device satisfies the condition, wherein the one or more packet rules are defined to examine any portion of a packet;

(b) providing the one or more packet rules;

(c) in response to a user, defining one or more role abstractions associated with an authenticated user, each role abstraction representing a role of an authenticated user with respect to the communications network for controlling usage of network resources on the communications network by the authenticated user, and each role abstraction including a set of one or more packet rules; and

(d) providing the one or more role abstractions.

28. (Previously presented) The method of claim 27, further comprising an act of: (e) configuring a network device of the communications network with one or more packet rules according to one of the role abstractions.

29. (Previously presented) The method of claim 28, wherein act (e) comprises: configuring a port module of a switching device of the communications network with one or more packet rules according to one of the role abstractions.

30. (Cancelled)

31. (Previously presented) The method of claim 27, further comprising an act of: (e) distributing the one or more role abstractions to one or more network devices residing on the communications network.

32. (Cancelled)

33. (Previously presented) A system for controlling usage of network resources on a communications network based on the identity of an authenticated user, the system comprising:

- a rule editing module to create one or more packet rules for analyzing packets received at one or more devices of the communications network, each rule including a condition and action to be taken if a packet received at a device satisfies the condition, wherein the one or more packet rules are defined to examine any portion of a packet;
- a role editing module to create, in response to a user, one or more role abstractions associated with an authenticated user, each role abstraction representing a role of an authenticated user with respect to the communications network for controlling usage of network

resources on the communications network by the authenticated user, and each role abstraction including a set of one or more packet rules; and

storage means for storing one or more created role abstractions or one or more created packet rules.

34. (Original) The system of claim 33, further comprising: logic to configure a port module of a network device with one or more packet rules according to one of the role abstractions.

35. (Original) The system of claim 34, wherein the logic comprises: port configuration logic to configure a port module of a switching device with one or more packet rules according to one of the role abstractions.

36. (Cancelled)

37. (Original) The system of claim 33, further comprising: a distribution module to distribute the one or more role abstractions to one or more network devices residing on the communications network.

38. (Cancelled)

39. (Cancelled)

40. (Previously presented) A computer program product, comprising: a computer readable medium; and computer readable signals stored on the computer readable medium that define instructions that, as a result of being executed by a computer, instruct the computer to perform a process of controlling usage of network resources on a communications network based on the identity of an authenticated user, the process comprising acts of:

(a) creating one or more packet rules for analyzing packets received at one or more devices of the communications network, each rule including a condition and action to be taken if a packet received at a device satisfies the condition, wherein the one or more packet rules are defined to examine any portion of a packet;

(b) storing the one or more packet rules;

(c) in response to a user, creating one or more role abstractions associated with an authenticated user, each role abstraction representing a role of an authenticated user with respect to the communications network for controlling usage of network resources on the communications network by the authenticated user, and each role abstraction including a set of one or more packet rules; and

(d) storing the one or more role abstractions.